Form 3160-3 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB No. 1004-0136 Expires July 31, 2010

BUREAU OF	LAND MANAGEMEN	ľ

5. Lease Serial No. UTU02270A

APPLICATION FOR PERMIT	6. If Indian, Allottee or Tribe Name		
la. Type of Work: ☑ DRILL ☐ REENTER		7. If Unit or CA Agreement, Name NATURAL BUTTES UN	and No.
1b. Type of Well: ☐ Oil Well Gas Well ☐ Oth	er Single Zone Multiple Zone	8. Lease Name and Well No. NBU 440-01E	
2. Name of Operator Contact:	KAYLENE R GARDNER gardner@eogresources.com	9. API Well No. 43047-3	1857
3a. Address 1060 EAST HIGHWAY 40 VERNAL, UT 84078	3b. Phone No. (include area code) Ph: 435-781-9111	10. Field and Pool, or Exploratory NATURAL BUTTES	
4. Location of Well (Report location clearly and in accorda	nce with any State requirements.*)	11. Sec., T., R., M., or Blk. and Sur	vey or Area
At surface NWSE 1882FSL 1931FEL	39.97494 N Lat, 109.61144 W Lon	Sec 1 T10S R20E Mer SLI	3
At proposed prod. zone NWSE 1882FSL 1931FEL	39.97494 N Lat, 109.61144 W Lon		
14. Distance in miles and direction from nearest town or post of 45.5 MILES SOUTH OF VERNAL, UTAH	office*	12. County or Parish UINTAH	13. State UT
 Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 758 	16. No. of Acres in Lease 2167.00	17. Spacing Unit dedicated to this v	vell
 Distance from proposed location to nearest well, drilling, completed, applied for, on this lease, ft. 1710 	19. Proposed Depth 7853 MD	20. BLM/BIA Bond No. on file NM 2308	
21. Elevations (Show whether DF, KB, RT, GL, etc. 4988 GL	22. Approximate date work will start	23. Estimated duration 45 DAYS	
	24. Attachments		
The following, completed in accordance with the requirements o	f Onshore Oil and Gas Order No. 1, shall be attached to	this form:	

1. Well plat certified by a registered surveyor.

 A Drilling Plan.
 A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).

- Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- Operator certification Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature (Electronic Submission	Name (Printed/Typed) KAYLENE R GARDNER Ph: 435-781-9111	Date 11/28/2007
LEAD REGULATORY ASSISTANT		
Approved (by (Signature)	Name (Printed/Typed) BRADLEY G. HILL	Date 12-06-07
Title	Office ENVIRONMENTAL MANAGER	

Application approval does not warrant or certify the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Electronic Submission #57310 verified by the BLM Well Information System For EOG RESOURCES, INC., sent to the Vernal

RECEIVED


Federal Approval of this Action is Necessary

NOV 3 0 2007

DIV. OF OIL, GAS & MINING

618427X 44256924 39.974958 -109.610832

** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **



NATURAL BUTTES UNIT 440-01E NW/SE, SEC. 1, T10S, R20E, S.L.B.&M.. UINTAH COUNTY, UTAH

1. & 2. ESTIMATED TOPS & ANTICIPATED OIL, GAS, & WATER ZONES:

FORMATION	TVD-RKB (ft)	Objective	Lithology	
Green River	1,425		Shale	
Wasatch	4,799	Primary	Sandstone	Gas
Chapita Wells	5,450	Primary	Sandstone	Gas
Buck Canyon	6,138	Primary	Sandstone	Gas
North Horn	6,862	Primary	Sandstone	Gas
KMV Price River	7,836		Sandstone	
TD	7,853			

Estimated TD: 7,853' or 200'± below Price River top Anticipated BHP: 4,288 Psig

- 1. Fresh Waters may exist in the upper, approximately 1,000 ft \pm of the Green River Formation, with top at about 2,000 ft \pm .
- 2. Cement isolation is installed to surface of the well isolating all zones by cement.

3. PRESSURE CONTROL EQUIPMENT:

Production Hole – 5000 Psig

BOP schematic diagrams attached.

4. CASING PROGRAM:

CASING	Hole Size	<u>Length</u>	<u>Size</u>	WEIGHT	<u>Grade</u>	Thread	Rating Collapse	<u>Factor</u> <u>Burst</u>	<u>Tensile</u>
Conductor	17 ½"	0 – 45'	13 3/8"	48.0#	H-40	STC	770 PSI	1730 PSI	322,000#
Surface	12 1/4"	0' - 2,300' KB±	9-5/8"	36.0#	J-55	STC	2020 PSI	3520 Psi	394,000#
Production	7-7/8"	Surface – TD	4-1/2"	11.6#	N-80	LTC	6350 PSI	7780 Psi	233,000#
				l .					

Note: $12-\frac{1}{4}$ " surface hole will be drilled to a total depth of 200'± below the base of the Green River lost circulation zone and cased w/9-5%" as shown to that depth. Drilled depth may be shallower or deeper than the 2300' shown above depending on the actual depth of the loss zone.

All casing will be new or inspected.

NATURAL BUTTES UNIT 440-01E NW/SE, SEC. 1, T10S, R20E, S.L.B.&M.. UINTAH COUNTY, UTAH

5. Float Equipment:

Surface Hole Procedure (0'- 2300'±)

Guide Shoe

Insert Float Collar (PDC drillable)

Centralizers: 1-5' above shoe, top of its. #2 and #3 then every 5th joint to surface. (15 total)

Production Hole Procedure (2300'± - TD):

Float shoe, 1 joint casing, float collar and balance of casing to surface. 4-½", 11.6#, N-80 or equivalent marker collars or short casing joints to be placed at top of Price River and 400' above top of Wasatch. Centralizers to be placed 5' above shoe on joint #1, top of joint #2, and every 2nd joint to 400' above Wasatch Island top. Thread lock float shoe, top and bottom of float collar, and top of 2nd joint.

6. MUD PROGRAM

Surface Hole Procedure (Surface - 2300'±):

Air/air mist or aerated water.

<u>Production Hole Procedure (2300' \pm - TD):</u> Anticipated mud weight 9.5 – 10.5 ppg depending on actual wellbore conditions encountered while drilling.

A closed mud system will be utilized. A bentonite gelled water mud system will be used to control viscosity w/PHPA polymer used for supplemental viscosity and clay encapsulation/inhibition. Water loss will be maintained at <15cc's using white starch or PAC. Bactericides will be used as needed. Anticipated pH will range from 9.0-10.0. Mud weight will be adjusted as necessary for well control. Deflocculants/thinners will be used as necessary to maintain mud quality. LCM sweeps will be utilized as necessary to control lost circulation and mud loss. CO2 contamination, if encountered, will be treated with lime and gypsum.

7. VARIANCE REQUESTS:

Reference: Onshore Oil and Gas Order No. 2 – Item E: Special Drilling Operations

EOG Resources, Inc. requests a variance to regulations requiring the blooie line to be 100' in length. Due to reduce location excavation, the blooie line will be approximately 75' in length

NATURAL BUTTES UNIT 440-01E NW/SE, SEC. 1, T10S, R20E, S.L.B.&M.. **UINTAH COUNTY, UTAH**

8. EVALUATION PROGRAM:

Logs:

Lead:

f , >

Mud log from base of surface casing to TD.

Cased-hole Logs:

Cased-hole logs will be run in lieu of open-hole logs consisting of the following:

Cement Bond / Casing Collar Locator and Pulsed Neutron

9. CEMENT PROGRAM:

Surface Hole Procedure (Surface - 2300'±):

185 sks Class "G" cement with 16% Gel, 10 #/sx Gilsonite, 3% Salt, 2% CaCI₂, 3 lb/sx GR3

1/4 #/sx Flocele mixed at 11 ppg, 3.82 ft³/sk. yield, 23 gps water.

207 sks Class "G" cement with 2% CaCI₂, ½#/sk Flocele mixed at 15.6 ppg, 1.18 ft³/sk., 5.2 Tail:

gps water.

Top Out: As necessary with Class "G" cement with 2% CaCI₂, ½#/sk Flocele mixed at 15.6 ppg, 1.18

ft³/sk., 5.2 gps water.

Cement volumes will be calculated to bring lead cement to surface and tail cement to Note:

500'above the casing shoe.

Production Hole Procedure (2300'± - TD)

143 sks: Hi-Lift "G" w/12% D20 (Bentonite), 1% D79 (Extender), 5% D44 Lead:

(Salt),0.2% D46 (Antifoam), 0.25% D112 (Fluid Loss Additive), 0.25 pps D29

(cello flakes) mixed at 11.0 ppg, 3.91 ft³/sk., 24.5 gps water.

622 sks: 50:50 Poz "G" w/ 2% D20 (Bentonite), 0.1% D46 (Antifoam), 0.075% D13 Tail:

(Retarder), 0.2% D167 (Fluid Loss Additive), 0.2% D65 (Dispersant), mixed at

14.1 ppg, $1.28 \text{ ft}^3/\text{sk.}$, 5.9 gps water.

The above number of sacks is based on gauge-hole calculation. Note:

Lead volume to be calculated to bring cement to 200'± above 9-5/8" casing shoe. Tail volume to be calculated to bring cement to 400'± above top of Wasatch.

Final Cement volumes will be based upon gauge-hole plus 45% excess.

NATURAL BUTTES UNIT 440-01E NW/SE, SEC. 1, T10S, R20E, S.L.B.&M.. UINTAH COUNTY, UTAH

10. ABNORMAL CONDITIONS:

Surface Hole (Surface - 2300'±):

Lost circulation

Production Hole (2300'± - TD):

Sloughing shales, lost circulation and key seat development are possible in the Wasatch Formation.

11. STANDARD REQUIRED EQUIPMENT:


- A. Choke Manifold
- B. Upper and Lower Kelly Cock
- C. Stabbing Valve
- D. Visual Mud Monitoring

12. HAZARDOUS CHEMICALS:

No chemicals subject to reporting under SARA title III in an amount equal to or greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling of this well. Furthermore, no extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will be used, produced, stored, transported, or disposed of in association with the drilling of this well.


(Attachment: BOP Schematic Diagram)

EOG RESOURCES 11" 5,000 PSI W.P. BOP CONFIGURATION



EOG RESOURCES CHOKE MANIFOLD CONFIGURATION W/ 5,000 PSI WP VALVES

PAGE 2 0F 2



4" 5,000 PSI CHOKE LINE FROM HCR VALVE

Testing Procedure:

- 1. BOP will be tested with a professional tester to conform to Onshore Order #2.
- 2. Blind and Pipe rams will be tested to rated working pressure, 5,000 psi.
- 3. Annular Preventer will be tested to 50% working pressure, 2,500 psi. Casing will be tested to 0.22 psi / ft. or 1,500 psi. Not to exceed 70% of burst strength, whichever is greater.
- 4. All lines subject to well pressure will be tested to the same pressure as blind and pipe rams.
- 5. All BOPE specifications and configurations will meet Onshore Order #2 requirements.



Natural Buttes Unit 440-01E NWSE, Section 1, T10S, R20E Uintah County, Utah

SURFACE USE PLAN

The well pad is approximately 375-feet long with a 261-foot width, containing 2.25 acres more or less. The well access road is approximately 1584 feet long with a 40-foot right-of-way, disturbing approximately 1.45 acres. New surface disturbance associated with the well pad and access road is estimated to be 3.7 acres. The pipeline is approximately 1090 feet long with a 20-foot right-of-way disturbing approximately .50 acres.

1. EXISTING ROADS:

- A. See attached Plats showing directional reference stakes on location, and attached TOPO Map "B" showing access to location from existing roads.
- B. The proposed well site is located approximately 45.2 miles south of Vernal, Utah See attached TOPO Map "A".
- C. Refer to attached Topographic Map "A" showing labeled access route to location.
- D. Existing roads will be maintained and repaired as necessary.

2. PLANNED ACCESS ROAD:

- A. The access road will be approximately 1584' in length, Culvert's shall be installed as needed. See attached Topo B.
- B. The access road has a 40-foot ROW w/18 foot running surface.
- C. Maximum grade of the new access road will be 8 percent.
- D. No turnouts will be required.
- E. Road drainage crossings shall be of the typical dry creek drainage crossing type.
- F. No bridges, or major cuts and fills will be required.
- G. The access road will be dirt surface.
- H. No gates, cattleguards, or fences will be required or encountered.
- A 40-foot permanent right-of-way is requested. No surfacing material will be used.

J. No additional storage areas will be needed for storing equipment, stockpiling, or vehicle parking.

All travel will be confined to existing access road rights-of-way.

New or reconstructed roads will be centerlined – flagged at time of location staking. Access roads and surface disturbing activities will conform to standards outlined in the Bureau of Land Management and Forest Service publication: Surface Operating Standards for Oil and Gas Exploration and Development, Fourth Edition and/or BLM Manual Section 9113 concerning road construction standards on projects subject to federal jurisdiction.

The road shall be constructed/upgraded to meet the standards of the anticipated traffic flow and all-weather road requirements. Construction/upgrading shall include ditching, draining, graveling, crowning, and capping the roadbed as necessary to provide a well constructed safe road. Prior to upgrading, the road shall be cleared of any snow cover and allowed to dry completely. Traveling off the 40-foot right-of-way will not be allowed. Road drainage crossings shall be of the typical dry creek drainage crossing type. Crossings shall be designed so they will not cause siltation or accumulation of debris in the drainage crossing nor shall the roadbed block the drainages. Erosion of drainage ditches by runoff water shall be prevented by diverting water off at frequent intervals by means of cutouts. Upgrading shall not be allowed during muddy conditions. Should mud holes develop, they shall be filled in and detours around then avoided.

As operator, EOG Resources, Inc. shall be responsible for all maintenance on cattleguards, or gates associated with this oil and/or gas operation.

Traveling off the 40-foot right-of-way will not be allowed. The access road and associated drainage structures will be constructed and maintained in accordance with road guidelines contained in the joint BLM/USFS publication: Surface Operating Standards for Oil and Gas Exploration and Development, Fourth Edition, and/or BLM Manual Section 9113 concerning road construction standards on projects subject to federal jurisdiction. During the drilling and production phase of operations, the road surface and shoulders will be kept in a safe and useable condition and drainage ditches and culverts will be kept clear and free flowing.

No off lease right-of-way will be required – The entire length of the access road and pipeline are located with Federal Lease UTU02270-A

3. LOCATION OF EXISTING WELLS WITHIN A ONE-MILE RADIUS:

See attached TOPO map "C" for the location of wells within a one-mile radius.

4. LOCATION OF EXISTING AND/OR PROPOSED PRODUCTION FACILITIES:

A. On Well Pad

1. Production facilities will be set on location if the well is successfully completed for production. Facilities will consist of wellhead valves, combo separator-dehy unit with meter, two (2) 400-bbl vertical tanks and attaching piping.

2. Gas gathering lines – A 4" gathering line will be buried from dehy to the edge of the location.

B. Off Well Pad

- 1. Proposed pipeline will transport natural gas.
- 2. The pipeline will be a permanent feeder line.
- 3. The length of the proposed pipeline is 1090' x 40'. The proposed pipeline leaves the southern edge of the well pad (Lease UTU02270-A) proceeding in a southerly direction for an approximate distance of 1090' tieing into an existing pipeline in the SESE of Section 1, T10S, R20E. Pipe will be 4" NOM, 0.156 wall, Grade X42, Zap-Lock, electric weld with a 35 mil X-Tru coating.
- 4. Proposed pipeline will be a 4" OD steel, zap-lok line laid on the surface
- 5. Proposed pipeline will be laid on surface.
- 6. A 20-foot permanent pipeline right-of-way is requested. A 40-foot temporary pipeline right-of-way for construction purposes is requested, the temporary right-of-way will be utilized for a 10-day period.
- 7. The proposed pipeline route begins in the NWSE of section 1, township 10S, range 20E, proceeding southerly for an approximate distance of 1090' to the NWSE of section 1, township 10S, range 20E.
- 8. Pipeline will be coupled using the Zap lock method. No additional off-pad facilities will be required.

All permanent (on site for six months or longer) structures constructed or installed (including pumping units) will be painted a flat, non-reflective, earthtone color to match one of the standard environmental colors, as determined by the Rocky Mountain Five State Interagency Committee. All facilities will be painted within 6 months of installation. All facilities will be painted with Carlsbad Canyon. Facilities required to comply with O.S.H.A. (Occupational Safety and Health Act) will be excluded.

5. LOCATION AND TYPE OF WATER SUPPLY:

- A. Water supply will be from Bonanza Power Plant water source in Sec 26, T8S, R23E, Uintah County, UT (State Water Right # 49-225(A31368)). Water will be hauled by a licensed trucking company.
- B. Water will be hauled by a licensed trucking company.
- C. No water well will be drilled on lease.

6. Source of Construction Materials:

- A. All construction material for this pipeline will be of native borrow and soil accumulated during the construction of the location.
- B. No mineral materials will be required.

7. METHODS OF HANDLING WASTE DISPOSAL:

A. METHODS AND LOCATION

- 1. Cuttings will be confined in the reserve pit.
- A portable toilet will be provided for human waste during the drilling and completion of the well. Disposal will be at the Vernal sewage disposal plant.
- 3. Burning will not be allowed. Trash and other waste material will be contained in a wire mesh cage and disposed of at the Uintah County Landfill.
- 4. Produced wastewater will be confined to a lined pit or storage tank for a period not to exceed 90 days after initial production. After the 90 day period, the produced water will be contained in a tank on location and then disposed of at one of the following locations: Natural Buttes Unit 21-20B SWD, Ace Disposal, CWU 550-30N SWD, CWU 2-29 SWD, Red Wash Evaporation Ponds 1, 2, 3 and 4, or EOG Resources, Inc. drilling operations (Chapita Wells Unit, Natural Buttes Unit & Stagecoach Unit).
- 5. All chemicals will be disposed of at an authorized disposal site. Drip pans and absorbent pads will be used on the drilling rig to avoid leakage of oil to the pit.
- B. Water from drilling fluids and recovered during testing operations will be disposed of by either evaporating in the reserve pit, through natural or artificial methods, or removed and disposed of at an authorized disposal site. Introduction of well bore hydrocarbons to the reserve pit will be avoided by flaring them off in the flare pit at the time of recovery.

The reserve pit will be constructed so as not to leak, break, or allow discharge. If the reserve pit requires padding prior to lining (due to rocky conditions) felt padding will be used.

The reserve pit shall be lined with felt, and a 16-millimeter plastic liner. Sufficient bedding (i.e. weed free straw, or hay; felt; polyswell or soil) will be used to cover any rocks. The liner will overlap the pit walls and be covered with dirt and/or rocks to hold it in place. No trash, scrap pipe, etc., that could puncture the liner will be disposed of in the pit. More stringent protective requirements may be deemed necessary by the A.O.

EOG Resources, Inc. maintains a file, per 29 CFR 1910.1200 (g) containing current Material Safety Data Sheets (MSDS) for all chemicals, compounds, and/or substances which are used during the course of construction, drilling, completion, and production

operations for this project. Hazardous materials (substances) which may be found at the site may include drilling mud and cementing products which are primarily inhalation hazards, fuels (flammable and/or combustible), materials that may be necessary for well completion/ stimulation activities such as flammable or combustible substances and acids/gels (corrosives). The opportunity for Superfund Amendments and Reauthorization Act (SARA) listed Extremely Hazardous Substances (EHS) at the site is generally limited to proprietary treating chemicals. All hazardous and EHS and commercial preparations will be handled in an appropriate manner to minimize the potential for leaks or spills to the environment.

No chemicals subject to reporting under SARA Title III (hazardous materials) in an amount greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completion of the well. Furthermore, extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will not be used, produced, stored, transported, or disposed of in association with the drilling, testing or completion of the well.

8. ANCILLARY FACILITIES:

None anticipated.

9. WELL SITE LAYOUT:

- A. Refer to attached well site plat for related topography cuts and fills and cross sections.
- B. Refer to attached well site plat for rig layout and soil material stockpile location as approved on On-site.
- C. Refer to attached well site plat for rig orientation, parking areas, and access road.

The reserve pit will be located on the south corner of the location. The flare pit will be located downwind of the prevailing wind direction on the south side of the location, a minimum of 100 feet from the wellhead and 30 feet from the reserve pit fence.

The stockpiled pit topsoil (first six inches) will be stored separate from the location topsoil. The stockpiled location topsoil will be stored in a location providing easy access for interim reclamation and protection of the topsoil. Upon completion of construction, the stockpiled topsoil from the location will be broadcast seeded with the approved seed mixture from this location and then walked down with a Caterpillar tractor.

Access to the well pad will be from the east.

FENCING REQUIREMENTS:

All pits will be fenced according to the following minimum standards:

- A. Thirty-nine inch net wire shall be used with at least one strand of barbed wire on top of the net wire. (Barbed wire is not necessary if pipe or some type of reinforcement rod is attached to the top of the entire fence.)
- B. The net wire shall be no more than 2 inches above the ground. The barbed wire strand shall be 3 inches above the net wire. Total height of the fence shall be at least 42 inches
- C. Corner posts shall be cemented and/or braced in such a manner as to keep the fence tight at all times.
- D. Standard steel, wood, or pipe posts shall be used between the corner braces. Maximum distances between any two posts shall be no greater than 16 feet.
- E. All wire shall be stretched by using a stretching device before it is attached to the corner posts.

The reserve pit fencing will be on the three sides during drilling operations and on the fourth side when the rig moves off location. Pits will be fenced and maintained until clean-up.

Each existing fence to be crossed by the access road shall be braced and tied off before cutting so as to prevent slacking of the wire. The opening shall be closed temporarily as necessary during construction to prevent the escape of livestock, and, upon completion of construction, the fence shall be repaired to BLM or SMA specifications. A cattleguard with an adjacent 16 foot gate shall be installed in any fence where a road is regularly traveled. If the well is a producer, the cattleguards (shall/shall not) be permanently counted on concrete bases. Prior to crossing any fence located on Federal land, or any fence between Federal land and private land, the operator will contact the BLM, who will in turn contact the grazing permittee or owner of said fence and offer him/her the opportunity to be present when the fence is cut in order to satisfy himself/herself that the fence is adequately braced and tied off.

10. PLANS FOR RECLAMATION OF THE SURFACE:

A. Interim Reclamation (Producing Location)

Immediately upon well completion, the location and surrounding area will be cleared of all unused tubing, equipment, debris, materials, trash, and junk not required for production.

Immediately upon well completion, any hydrocarbons on the pit shall be removed in accordance with CFR 3162.7-1.

If a plastic nylon reinforced liner is used, it shall be torn and perforated before backfilling of the reserve pit.

The reserve pit and that portion of the location not needed for production facilities/operations will be recontoured to the approximate natural contours. The

reserve pit will be reclaimed within 90 days from the date of the well completion, or as soon as environmental conditions allow. Before any dirt takes place, the reserve pit must be completely dry and free of all foreign obstacles.

The stockpiled pit topsoil will then be spread over the pit area and broadcast seeded with the prescribed seed mixture for this location. The seeded area will then be walked down with a cat.

Seed Mixture	Drilled Rate (lbs./acre PLS*)		
HyCrest Wheatgrass	9.0		
Prostrate Kochia	3.0		

^{*}Pure live seed (PLS) formula: percent of purity of seed mixture times percent germination of seed mixture equals portion of seed mixture that is PLS.

B. Dry Hole/Abandoned Location

At such time as the well is plugged and abandoned, the operator will submit a subsequent report of abandonment and the BLM will attach the appropriated surface rehabilitation conditions of approval.

Seed Mixture	Drilled Rate (Ibs./acre PLS*)		
Gardner Saltbush	3.0		
Shadscale	3.0		
HyCrest Wheatgrass	3.0		

^{*}Pure live seed (PLS) formula: percent of purity of seed mixture times percent germination of seed mixture equals portion of seed mixture that is PLS.

11. SURFACE OWNERSHIP:

Surface ownership of the proposed well site, access road, and pipeline route is as follows:

Bureau of Land Management

12. OTHER INFORMATION:

A. EOG Resources, Inc. will inform all persons in the area who are associated with this project that they are subject to prosecution for knowingly disturbing historic or archaeological sites, or for collecting artifacts. If historic or archaeological materials are uncovered during construction, the operator will immediately stop work that might further disturb such materials, and contact the Authorized Officer. Within five working days the Authorized Officer will inform the operator as to:

- Whether the materials appear eligible for the National Register of Historic Places:
- The mitigation measures the operator will likely have to undertake before the site can be used.
- A time frame for the Authorized Officer to complete an expedited review under 36 CFR 800.11 to confirm, through the State Historic Preservation Officer, that the findings of the Authorized Officer are correct and that mitigation is appropriate.

If the operator wished, at any time, to relocate activities to avoid the expense of mitigation and/or the delays associated with this process, the Authorized Officer will assume responsibility for whatever recordation and stabilization of the exposed materials that may be required. Otherwise, the operator will be responsible for mitigation costs. The Authorized Officer will provide technical and procedural guidelines for the conduct of mitigation. Upon verification from the Authorized Officer that required mitigation has been completed, the operator will then be allowed to resume construction.

- B. As operator, EOG Resources, Inc. will control noxious weeds along Right-of-Ways for roads, pipelines, well sites, or other applicable facilities. A list of noxious weeds will be obtained from the BLM administered land, a Pesticide Use proposal shall be submitted, and given approval, prior to the application or herbicides or other pesticides or possible hazardous chemicals.
- C. Drilling rigs and/or equipment used during drilling operations on this well site will not be stacked or stored on BLM lands after the conclusion of drilling operations or at any other time without BLM authorization. However, if BLM authorization is obtained, it is only a temporary measure to allow time to make arrangements for permanent storage on commercial facilities. (The BLM does not seek to compete with private industry. There are commercial facilities available for stacking and storing drilling rigs.)
- D. The drilling rig and ancillary equipment will be removed from the location prior to commencement of completion operations. Completion operations will be conducted utilizing a completion/workover rig.

All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws, regulations, Onshore Oil and Gas Orders, the approved Plan of Operations, and any applicable Notice of Lessees. The operator is fully responsible for the actions of its subcontractors. A complete copy of the approved "Application for Permit to Drill" will be furnished to the field representative(s) to ensure compliance and shall be on location during all construction and drilling operations.

Construction activity will not be conducted using frozen or saturated soils material or during periods when watershed damage is likely to occur.

If the existing access road, proposed access road, and proposed pad are dry during construction, drilling, and completion activities, water will be applied to help facilitate compaction during construction and to minimize soil loss as a result of wind erosion.

A cultural resources survey was conducted and will be submitted by Montgomery Archaeological Consultants. A paleontological survey was conducted and will be submitted by Intermountain Paleo .

LESSEE OR OPERATOR'S REPRESENTATIVE AND CERTIFICATION:

PERMITTING AGENT

Kaylene R. Gardner EOG Resources, Inc. P.O. Box 1815 Vernal, UT 84078 (435) 781-9111

All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws, regulations, Onshore Oil and Gas Orders, the approved plan of operations, and any applicable Notice to Lessees. The operator is fully responsible for the actions of his subcontractors. A copy of these conditions will be furnished to the field representative to insure compliance.

The operator or his/her contractor shall contact the BLM office at (435) 781-4400 forty-eight (48) hours prior to construction activities.

CERTIFICATION:

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions which currently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by EOG Resources, Inc. and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of a false statement.

Please be advised that EOG Resources, Inc. is considered to be the operator of the Natrual Buttes Unit 440-01E Well, located in the NWSE, of Section 1, T10S, R20E, Uintah County, Utah; Federal land and minerals; and is responsible under the terms and conditions of the lease for the operations conducted upon the leased lands. Bond Coverage is under Bond # NM 2308.

11/28/2007


Date


ad Regulatory Assistant

EOG RESOURCES, INC. NBU #440-1E SECTION 1, T10S, R20E, S.L.B.&M.

PROCEED IN A WESTERLY DIRECTION FROM VERNAL, UTAH ALONG U.S. HIGHWAY 40 APPROXIMATELY 14.0 MILES TO THE JUNCTION OF STATE HIGHWAY 88; EXIT LEFT AND PROCEED IN A SOUTHERLY DIRECTION APPROXIMATELY 17.0 MILES TO OURAY, UTAH; PROCEED IN A SOUTHERLY DIRECTION ON THE SHEEP RIDGE ROAD APPROXIMATELY 11.2 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE EAST: TURN RIGHT AND PROCEED IN A EASTERLY DIRECTION APPROXIMATELY 0.8 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE NORTHEAST; TURN RIGHT AND PROCEED IN AN NORTHERLY DIRECTION APPROXIMATELY 1.2 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE SOUTHWEST; TURN LEFT AND PROCEED IN A SOUTHWESTERLY, THEN NORTHWESTERLY DIRECTION APPROXIMATELY 0.8 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE WEST; TURN LEFT AND PROCEED IN A WESTERLY DIRECTION APPROXIMATELY 0.2 MILES TO BEGINNING OF THE PROPOSED ACCESS TO THE NORTH: FOLLOW ROAD FLAGS IN A NORTHERLY DIRECTION APPROXIMATELY 0.3 MILES TO THE PROPOSED LOCATION.

TOTAL DISTANCE FROM VERNAL, UTAH TO THE PROPOSED WELL LOCATION IS APPROXIMATELY 45.5 MILES.





EOG RESOURCES, INC. FIGURE #3 PRODUCTION FACILITY LAYOUT FOR NBU #440-1E SECTION 1, T10S, R20E, S.L.B.&M. 1882' FSL 1931' FEL SCALE: 1" = 50' DATE: 10-17-07 Drawn By: C.H. COMBO UNIT WELL HEAD

RE-HABED AREA

UINTAH ENGINEERING & LAND SURVEYING 85 So. 200 East * Vernal, Utah 84078 * (435) 789-1017

Access Road

EOG RESOURCES, INC. NBU #440-1E

LOCATED IN UINTAH COUNTY, UTAH **SECTION 1, T10S, R20E, S.L.B.&M.**




PHOTO: VIEW FROM CORNER #5 TO LOCATION STAKE

CAMERA ANGLE: NORTHEASTERLY




PHOTO: VIEW FROM BEGINNING OF PROPOSED ACCESS

CAMERA ANGLE: NORTHEASTERLY





Uintah Engineering & Land Surveying 85 South 200 East Vernal, Utah 84078 435-789-1017 uels@uelsinc.com


LOCATION PHOTOS


РНОТО

TAKEN BY: C.R.. DRAWN BY: Z.L. REVISED: 00-00-00











WORKSHEET APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 11/30/2007	API NO. ASSIGNED: 43-047-39857
WELL NAME: NBU 440-01E OPERATOR: EOG RESOURCES, INC. (N9550) CONTACT: KAYLENE GARDNER	PHONE NUMBER: 435-781-9111
PROPOSED LOCATION:	INSPECT LOCATN BY: / /
NWSE 01 100S 200E	Tech Review Initials Date
SURFACE: 1882 FSL 1931 FEL BOTTOM: 1882 FSL 1931 FEL	Engineering
COUNTY: UINTAH	Geology
LATITUDE: 39.97496 LONGITUDE: -109.6108 UTM SURF EASTINGS: 618627 NORTHINGS: 44256	92 Surface
FIELD NAME: NATURAL BUTTES (630 LEASE TYPE: 1 - Federal LEASE NUMBER: UTU02270A SURFACE OWNER: 1 - Federal	PROPOSED FORMATION: PRRV COALBED METHANE WELL? NO
Plat Plat Bond: Fed[1] Ind[] Sta[] Fee[] (No. NM 2308 Potash (Y/N) Oil Shale 190-5 (B) or 190-3 or 190-13 Water Permit (No. 49-225 RDCC Review (Y/N) (Date: AMA Fee Surf Agreement (Y/N) AMA Intent to Commingle (Y/N)	LOCATION AND SITING: R649-2-3. Unit: NATURAL BUTTES W R649-3-2. General
STIPULATIONS: 1- Jeden 9 2. Oil 14	erano Cale





State of Utah DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER Executive Director

Division of Oil Gas and Mining

JOHN R. BAZA
Division Director

December 6, 2007

EOG Resources, Inc. 1060 East Highway 40 Vernal, UT 84078

Re:

NBU 440-01E Well, 1882' FSL, 1931' FEL, NW SE, Sec. 1, T. 10 South, R. 20 East,

Uintah County, Utah

Gentlemen:

Pursuant to the provisions and requirements of Utah Code Ann.§ 40-6-1 *et seq.*, Utah Administrative Code R649-3-1 *et seq.*, and the attached Conditions of Approval, approval to drill the referenced well is granted.

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date. The API identification number assigned to this well is 43-047-39857.

Sincerely,

Gil Hunt

Associate Director

pab Enclosures

cc:

Uintah County Assessor

Bureau of Land Management, Vernal Office



Operator:	EOG Resources, Inc.			
Well Name & Number	NBU 440-01E			
API Number:	43-047-39857			
Lease:	UTU02270A			
Location: <u>NW SE</u>	Sec. 1	T. 10 South	R. <u>20 East</u>	

Conditions of Approval

1. General

Compliance with the requirements of Utah Admin. R. 649-1 *et seq.*, the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

2. Notification Requirements

Notify the Division within 24 hours of spudding the well.

• Contact Carol Daniels at (801) 538-5284.

Notify the Division prior to commencing operations to plug and abandon the well.

• Contact Dustin Doucet at (801) 538-5281 office (801) 733-0983 home

3. Reporting Requirements

All required reports, forms and submittals will be promptly filed with the Division, including but not limited to the Entity Action Form (Form 6), Report of Water Encountered During Drilling (Form 7), Weekly Progress Reports for drilling and completion operations, and Sundry Notices and Reports on Wells requesting approval of change of plans or other operational actions.

- 4. State approval of this well does not supersede the required federal approval, which must be obtained prior to drilling.
- 5. In accordance with Order in Cause No. 190-5(b) dated October 28, 1982, the Operator shall comply with requirements of Rules R649-3-31 and R649-3-27 pertaining to Designated Oil Shale Areas. Additionally, the operator shall ensure that the surface and/or production casing is properly cemented over the entire oil shale interval as defined by Rule R649-3-31. The Operator shall report the actual depth the oil shale is encountered to the Division.

Form 3160-3 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

2007

FORM APPROVED OMB No. 1004-0136 Expires July 31, 2010

Lease Serial No. UTU02270A

APPLICATION FOR PERMIT TO DRILL OR R	EENTE
--------------------------------------	-------

R 6. If Indian, Allottee or Tribe Name DRILL If Unit or CA Agreement, Name and No. la. Type of Work: REENTER UTU63047A 8. Lease Name and Well No. NBU 440-1E Other 1b. Type of Well: Oil Well Multiple Zone ☐ Single Zone 9. API Well No. Name of Operato Contact: KAYLENE R GARDNER EOG RESOURCES INC E-Mail: KAYLENE_GARDNER@EOGRESOURCES.COM Field and Pool, or Exp 3a. Address b. Phone No. (include area code) 1060 EAST HIGHWAY 40 Ph: 435-781-9111 NATURAL BUTTES VERNAL, UT 84078 11. Sec., T., R., M., or Blk. and Survey or Area 4. Location of Well (Report location clearly and in accordance with any State requirements.*) At surface NWSE 1882FSL 1931FEL 39.97494 N Lat, 109.61144 W Lon Sec 1 T10S R20E Mer SLB SME: BLM At proposed prod. zone NWSE 1882FSL 1931FEL 39.97494 N Lat, 109.61144 W Lon 14. Distance in miles and direction from nearest town or post office* 12. County or Parish State 45.5 MILES SOUTH OF VERNAL, UTAH UINTAH UT 15. Distance from proposed location to nearest property or 16. No. of Acres in Lease 17. Spacing Unit dedicated to this well lease line, ft. (Also to nearest drig. unit line, if any) 758 2,167,030 18. Distance from proposed location to nearest well, drilling, 19. Proposed Depth 20. BLM/BIA Bond No. on file completed, applied for, on this lease, ft. 7853 MD NM2308 21. Elevations (Show whether DF, KB, RT, GL, etc. 22. Approximate date work will start 23. Estimated duration 45 DAYS 4988 GL

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

- 1. Well plat certified by a registered surveyor.
- 2. A Drilling Plan.
- 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).
- 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- Operator certification
- Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature (Electronic Submission)	Name (Printed/Typed) KAYLENE R GARDNER Ph: 435-781-9111	Date 11/28/2007
Title LEAD REGULATORY ASSISTANT		
Approved by (Signature)	Name (Printed/Typed) JERRY KENCEKA	001 ^{Pat} 02 2008
Assistant Field Manager I corde & Mineral Resources	Office VEDNAI FIELD OFFICE	
Application approval does not warrant or certify the applicant	holds legal or equitable title to those rights in the subject lease which would entitle the	e applicant to conduct

operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

> Electronic Submission #57310 verified by the BLM Well Information System For EOG RESOURCES INC, sent to the Vernal Committed to AFMSS for processing by CINDY SEVERSON on 11/28/2007 (08CXS0052AE) CEIVED

> > OCT 29 2008

DIV. OF OIL, GAS & MINING

UDO6M

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **



UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT VERNAL FIELD OFFICE



170 South 500 East

VERNAL, UT 84078 (435) 781-4400

CONDITIONS OF APPROVAL FOR APPLICATION FOR PERMIT TO DRILL

Company: EOG Resources Location: NWSE, Sec 1, T10S, R20E Well No: NBU 440-1E Lease No: UTU-02270A

API No: 43-047-39857 Agreement: Natural Buttes Unit

Title	Name	Office Phone Number	Cell Phone Number
Petroleum Engineer:	Matt Baker	(435) 781-4490	(435) 828-4470
Petroleum Engineer:	Michael Lee	(435) 781-4432	(435) 828-7875
Petroleum Engineer:	James Ashley	(435) 781-4470	(435) 828-7874
Petroleum Engineer:	Ryan Angus	(435) 781-4430	(435) 828-7368
Supervisory Petroleum Technician:	Jamie Sparger	(435) 781-4502	(435) 828-3913
NRS/Enviro Scientist:	Paul Buhler	(435) 781-4475	(435) 828-4029
NRS/Enviro Scientist:	Karl Wright	(435) 781-4484	(435) 828-7381
NRS/Enviro Scientist:	Holly Villa	(435) 781-4404	, ,
NRS/Enviro Scientist:	•	(435) 781-4476	
NRS/Enviro Scientist:	Chuck MacDonald	(435) 781-4441	(435) 828-7481
NRS/Enviro Scientist:	Jannice Cutler	(435) 781-3400	(435) 828-3544
NRS/Enviro Scientist:	Michael Cutler	(435) 781-3401	(435) 828-3546
NRS/Enviro Scientist:	Anna Figueroa	(435) 781-3407	(435) 828-3548
NRS/Enviro Scientist:	Verlyn Pindell	(435) 781-3402	(435) 828-3547
NRS/Enviro Scientist:	Darren Williams	(435) 781-4447	•
NRS/Enviro Scientist:	Nathan Packer	(435) 781-3405	(435) 828-3545
		Fax: (435) 781-3420	, ,

A COPY OF THESE CONDITIONS SHALL BE FURNISHED TO YOUR FIELD REPRESENTATIVE TO INSURE COMPLIANCE

All lease and/or unit operations are to be conducted in such a manner that full compliance is made with the applicable laws, regulations (43 CFR Part 3160), and this approved Application for Permit to Drill including Surface and Downhole Conditions of Approval. The operator is considered fully responsible for the actions of his subcontractors. A copy of the approved APD must be on location during construction, drilling, and completion operations. This permit is approved for a two (2) year period, or until lease expiration, whichever occurs first. An additional extension, up to two (2) years, may be applied for by sundry notice prior to expiration.

NOTIFICATION REQUIREMENTS

Location Construction (Notify Environmental Scientist)	-	Forty-Eight (48) hours prior to construction of location and access roads.
Location Completion (Notify Environmental Scientist)	-	Prior to moving on the drilling rig.
Spud Notice (Notify Petroleum Engineer)	-	Twenty-Four (24) hours prior to spudding the well.
Casing String & Cementing (Notify Supv. Petroleum Tech.)		Twenty-Four (24) hours prior to running casing and cementing all casing strings.
BOP & Related Equipment Tests (Notify Supv. Petroleum Tech.)	•	Twenty-Four (24) hours prior to initiating pressure tests.
First Production Notice (Notify Petroleum Engineer)	-	Within Five (5) business days after new well begins or production resumes after well has been off production for more than ninety (90) days.

Page 2 of 6 Well: NBU 440-1E 9/30/2008

SURFACE USE PROGRAM CONDITIONS OF APPROVAL (COAs)

General Surface COAs:

- If there is an active Gilsonite mining operation within 2 miles of the well location, operator shall notify the Gilsonite operator at least 48 hours prior to any blasting during construction.
- If paleontological materials are uncovered during construction, the operator is to immediately stop work and contact the Authorized Officer (AO). A determination will be made by the AO as to what mitigation may be necessary for the discovered paleontologic material before construction can continue.

Specific Surface COAs:

- Bury pipeline at all low water crossings.
- Permission from an authorized BLM representative will be required if construction or other operations occur during wet conditions that will lead to excessive rutting.
- Permission to clear all wildlife stipulations will only be approved by the BLM authorized officer during the specific timing for the species potentially affected by this action.
- Culverts and gravel may be installed as needed.
- No drilling or construction from may 15 to June 20 in order to protect pronghorn during the kidding period.
- A diversion ditch will be constructed from corner B to 6 until interim reclamation.

Page 3 of 6 Well: NBU 440-1E 9/30/2008

DOWNHOLE CONDITIONS OF APPROVAL

SITE SPECIFIC DOWNHOLE CONDITIONS OF APPROVAL

- The conductor pipe shall be set and cemented in a competent formation.
- A variance is granted for Onshore Order #2-Drilling Operations III. E. "Blooie line discharge 100 feet from well bore and securely anchored". Blooie line can be 75 feet. All other requirements in O.O. #2 III. E. Special Drilling Operations are applicable.
- Production casing cement shall be at a minimum 200 feet inside the surface casing. A CBL shall be run from TD to top of cement and a field copy shall be sent to this field office.
- The Gamma Ray log shall be run from TD to surface.

All provisions outlined in Onshore Oil & Gas Order #2 Drilling Operations shall be strictly adhered to. The following items are emphasized:

DRILLING/COMPLETION/PRODUCING OPERATING STANDARDS

- The spud date and time shall be reported orally to Vernal Field Office within 24 hours of spudding.
- Notify Vernal Field Office Supervisory Petroleum Engineering Technician at least 24 hours in advance of casing cementing operations and BOPE & casing pressure tests.
- Blowout prevention equipment (BOPE) shall remain in use until the well is completed or abandoned. Closing unit controls shall remain unobstructed and readily accessible at all times. Choke manifolds shall be located outside of the rig substructure.
- All BOPE components shall be inspected daily and those inspections shall be recorded in the daily drilling report. Components shall be operated and tested as required by Onshore Oil & Gas Order No. 2 to insure good mechanical working order. All BOPE pressure tests shall be performed by a test pump with a chart recorder and <u>NOT</u> by the rig pumps. Test shall be reported in the driller's log.
- BOP drills shall be initially conducted by each drilling crew within 24 hours of drilling out from under the surface casing and weekly thereafter as specified in Onshore Oil & Gas Order No. 2.
- Casing pressure tests are required before drilling out from under all casing strings set and cemented in place.
- No aggressive/fresh hard-banded drill pipe shall be used within casing.
- Cement baskets shall not be run on surface casing.
- The operator must report all shows of water or water-bearing sands to the BLM. If flowing
 water is encountered it must be sampled, analyzed, and a copy of the analyses submitted
 to the BLM Vernal Field Office.

Page 4 of 6 Well: NBU 440-1E 9/30/2008

• The operator must report encounters of all non oil & gas mineral resources (such as Gilsonite, tar sands, oil shale, trona, etc.) to the Vernal Field Office, in writing, within 5 working days of each encounter. Each report shall include the well name/number, well location, date and depth (from KB or GL) of encounter, vertical footage of the encounter and, the name of the person making the report (along with a telephone number) should the BLM need to obtain additional information.

- A complete set of angular deviation and directional surveys of a directional well will be submitted to the Vernal BLM office engineer within 30 days of the completion of the well.
- Chronologic drilling progress reports shall be filed directly with the BLM, Vernal Field Office
 on a weekly basis in sundry, letter format or e-mail to the Petroleum Engineers until the well
 is completed.
- A cement bond log (CBL) will be run from the production casing shoe to the top of cement and shall be utilized to determine the bond quality for the production casing. Submit a field copy of the CBL to this office.
- Please submit an electronic copy of all other logs run on this well in LAS format to UT_VN_Welllogs@BLM.gov. This submission will supersede the requirement for submittal of paper logs to the BLM.
- There shall be no deviation from the proposed drilling, completion, and/or workover program as approved. Safe drilling and operating practices must be observed. Any changes in operation must have prior approval from the BLM Vernal Field Office.

Page 5 of 6 Well: NBU 440-1E 9/30/2008

OPERATING REQUIREMENT REMINDERS:

- All wells, whether drilling, producing, suspended, or abandoned, shall be identified in accordance with 43 CFR 3162.6. There shall be a sign or marker with the name of the operator, lease serial number, well number, and surveyed description of the well.
- In accordance with 43 CFR 3162.4-3, this well shall be reported on the "Monthly Report of Operations" (Oil and Gas Operations Report ((OGOR)) starting with the month in which operations commence and continue each month until the well is physically plugged and abandoned. This report shall be filed in duplicate, directly with the Minerals Management Service, P.O. Box 17110, Denver, Colorado 80217-0110, or call 1-800-525-7922 (303) 231-3650 for reporting information.
- Should the well be successfully completed for production, the BLM Vernal Field office must be
 notified when it is placed in a producing status. Such notification will be by written
 communication and must be received in this office by not later than the fifth business day
 following the date on which the well is placed on production. The notification shall provide, as a
 minimum, the following informational items:
 - o Operator name, address, and telephone number.
 - Well name and number.
 - o Well location (1/4/4, Sec., Twn, Rng, and P.M.).
 - Date well was placed in a producing status (date of first production for which royalty will be paid).
 - The nature of the well's production, (i.e., crude oil, or crude oil and casing head gas, or natural gas and entrained liquid hydrocarbons).
 - o The Federal or Indian lease prefix and number on which the well is located; otherwise the non-Federal or non-Indian land category, i.e., State or private.
 - o Unit agreement and/or participating area name and number, if applicable.
 - o Communitization agreement number, if applicable.
- Any venting or flaring of gas shall be done in accordance with Notice to Lessees (NTL) 4A and needs prior approval from the BLM Vernal Field Office.
- All undesirable events (fires, accidents, blowouts, spills, discharges) as specified in NTL 3A will
 be reported to the BLM, Vernal Field Office. Major events, as defined in NTL3A, shall be
 reported verbally within 24 hours, followed by a written report within 15 days. "Other than Major
 Events" will be reported in writing within 15 days. "Minor Events" will be reported on the
 Monthly Report of Operations and Production.
- Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (BLM Form 3160-4) shall be submitted not later than 30 days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3162.4-1. Two copies of all logs run, core descriptions, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, shall be filed on BLM Form 3160-4. Submit with the well completion report a geologic report including,

Page 6 of 6 Well: NBU 440-1E 9/30/2008

at a minimum, formation tops, and a summary and conclusions. Also include deviation surveys, sample descriptions, strip logs, core data, drill stem test data, and results of production tests if performed. Samples (cuttings, fluid, and/or gas) shall be submitted only when requested by the BLM, Vernal Field Office.

- All off-lease storage, off-lease measurement, or commingling on-lease or off-lease, shall have prior written approval from the BLM Vernal Field Office.
- Oil and gas meters shall be calibrated in place prior to any deliveries. The BLM Vernal Field
 Office Petroleum Engineers will be provided with a date and time for the initial meter calibration
 and all future meter proving schedules. A copy of the meter calibration reports shall be
 submitted to the BLM Vernal Field Office. All measurement facilities will conform to the API
 standards for liquid hydrocarbons and the AGA standards for natural gas measurement. All
 measurement points shall be identified as the point of sale or allocation for royalty purposes.
- A schematic facilities diagram as required by Onshore Oil & Gas Order No. 3 shall be submitted
 to the BLM Vernal Field Office within 30 days of installation or first production, whichever occurs
 first. All site security regulations as specified in Onshore Oil & Gas Order No. 3 shall be
 adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively
 sealed in accordance with Onshore Oil & Gas Order No. 3.
- Any additional construction, reconstruction, or alterations of facilities, including roads, gathering
 lines, batteries, etc., which will result in the disturbance of new ground, shall require the filing of
 a suitable plan and need prior approval of the BLM Vernal Field Office. Emergency approval
 may be obtained orally, but such approval does not waive the written report requirement.
- No location shall be constructed or moved, no well shall be plugged, and no drilling or workover
 equipment shall be removed from a well to be placed in a suspended status without prior
 approval of the BLM Vernal Field Office. If operations are to be suspended for more than 30
 days, prior approval of the BLM Vernal Field Office shall be obtained and notification given
 before resumption of operations.
- Pursuant to Onshore Oil & Gas Order No. 7, this is authorization for pit disposal of water produced from this well for a period of 90 days from the date of initial production. A permanent disposal method must be approved by this office and in operation prior to the end of this 90-day period. In order to meet this deadline, an application for the proposed permanent disposal method shall be submitted along with any necessary water analyses, as soon as possible, but no later than 45 days after the date of first production. Any method of disposal which has not been approved prior to the end of the authorized 90-day period will be considered as an Incident of Noncompliance and will be grounds for issuing a shut-in order until an acceptable manner for disposing of said water is provided and approved by this office.
- Unless the plugging is to take place immediately upon receipt of oral approval, the Field Office Petroleum Engineers must be notified at least 24 hours in advance of the plugging of the well, in order that a representative may witness plugging operations. If a well is suspended or abandoned, all pits must be fenced immediately until they are backfilled. The "Subsequent Report of Abandonment" (Form BLM 3160-5) must be submitted within 30 days after the actual plugging of the well bore, showing location of plugs, amount of cement in each, and amount of casing left in hole, and the current status of the surface restoration.

FORM 9 STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING 5. LEASE DESIGNATION AND SERIAL NUMBER: UTU-02270-A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME: SUNDRY NOTICES AND REPORTS ON WELLS 7. UNIT or CA AGREEMENT NAME: Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals. Natural Buttes 1. TYPE OF WELL 8. WELL NAME and NUMBER: OIL WELL GAS WELL 🗸 OTHER Natural Buttes Unit 440-01E 2. NAME OF OPERATOR: 9 API NUMBER EOG Resources, Inc. 43-047-39857 3. ADDRESS OF OPERATOR PHONE NUMBER: 10. FIELD AND POOL, OR WILDCAT: 1060 East Highway 40 UT . 84078 Vernal (435) 781-9111 Natural Buttes 4. LOCATION OF WELL FOOTAGES AT SURFACE: 1882' FSL & 1931' FEL 39.974936 LAT 109.611444 LON COUNTY: Uintah QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: NWSE 10S 20E S.L.B. & M. STATE: UTAH CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 11. TYPE OF SUBMISSION TYPE OF ACTION ACIDIZE DEEPEN REPERFORATE CURRENT FORMATION 1 NOTICE OF INTENT (Submit in Duplicate) ALTER CASING FRACTURE TREAT SIDETRACK TO REPAIR WELL Approximate date work will start: CASING REPAIR NEW CONSTRUCTION TEMPORARILY ABANDON CHANGE TO PREVIOUS PLANS OPERATOR CHANGE TUBING REPAIR CHANGE TUBING PLUG AND ABANDON VENT OR FLARE SUBSEQUENT REPORT CHANGE WELL NAME PLUG BACK WATER DISPOSAL (Submit Original Form Only) CHANGE WELL STATUS PRODUCTION (START/RESUME) WATER SHUT-OFF Date of work completion: COMMINGLE PRODUCING FORMATIONS RECLAMATION OF WELL SITE OTHER: APD Extension Request CONVERT WELL TYPE **RECOMPLETE - DIFFERENT FORMATION** 12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. EOG Resources, Inc. respectfully requests the APD for the referenced well be extended for one year. Approved by the Utah Division of Oil, Gas and Mining

NAME (PLEASE PRINT) Mickenzie Thacker

SIGNATURE Will Will DATE Operations Clerk

DATE 11/13/2008

(This space for State use only)

(5/2000)

COPY SENT TO OPERATOR

Date: 11.18.2008

(See Instructions on Reverse Side)

RECEIVED

MOV 17 2003

Application for Permit to Drill Request for Permit Extension Validation (this form should accompany the Sundry Notice requesting permit extension)

API:

43-047-39857

Well Name: Natural Buttes Unit 440-01E Location: 1882 FSL & 1931 FEL (NWSE), SECTION 1, T Company Permit Issued to: EOG RESOURCES, INC. Date Original Permit Issued: 12/6/2007	10S, R20E S.L.B.&M				
The undersigned as owner with legal rights to drill on tabove, hereby verifies that the information as submitted approved application to drill, remains valid and does n	ed in the previously				
Following is a checklist of some items related to the appreciated.	oplication, which should be				
f located on private land, has the ownership changed, if so, has the surface agreement been updated? Yes□No□					
Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes ☐ No ☑					
Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? Yes□No☑					
Have there been any changes to the access route including ownership, or right- of-way, which could affect the proposed location? Yes□No☑					
Has the approved source of water for drilling changed? Yes□ No☑					
Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes□No☑					
s bonding still in place, which covers this proposed well? Yes ☑No□					
Midunii Thaller.) Signature	11/13/2008				
Signature	Date				
Fitle: Operations Clerk					
Representing: EOG Resources, Inc.					

RECEIVED NOV 17 2008 DIV. OF OIL, GAS & MINING

STATE OF UTAH		FORM 9		
	5.LEASE DESIGNATION AND SERIAL NUMBER: UTU02270A			
SUNDRY NOTICES AND REPORTS ON WELLS			6. IF INDIAN, ALLOTTEE OR TRIBE NAME:	
	sals to drill new wells, significantly deepen ex gged wells, or to drill horizontal laterals. Use		7.UNIT or CA AGREEMENT NAME: NATURAL BUTTES	
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: NBU 440-01E	
2. NAME OF OPERATOR: EOG Resources, Inc.		9. API NUMBER: 43047398570000		
3. ADDRESS OF OPERATOR: 1060 East Highway 40, Verna	al, UT, 84078 435 781-9111	PHONE NUMBER: 1 Ext	9. FIELD and POOL or WILDCAT: NATURAL BUTTES	
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1882 FSL 1931 FEL			COUNTY: UINTAH	
QTR/QTR, SECTION, TOWNSHI Qtr/Qtr: NWSE Section: 01	P, RANGE, MERIDIAN: Township: 10.0S Range: 20.0E Meridian: S		STATE: UTAH	
11. CHE	CK APPROPRIATE BOXES TO INDICATE	NATURE OF NOTICE, REPORT,	OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION		
✓ NOTICE OF INTENT Approximate date work will start:	☐ ACIDIZE ☐ CHANGE TO PREVIOUS PLANS	☐ ALTER CASING ☐ CHANGE TUBING	☐ CASING REPAIR ☐ CHANGE WELL NAME	
11/4/2009	☐ CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	CONVERT WELL TYPE	
SUBSEQUENT REPORT Date of Work Completion:	☐ OPERATOR CHANGE	FRACTURE TREAT PLUG AND ABANDON	NEW CONSTRUCTION□ PLUG BACK	
SPUD REPORT Date of Spud:	☐ PRODUCTION START OR RESUME ☐ REPERFORATE CURRENT FORMATION	RECLAMATION OF WELL SITE SIDETRACK TO REPAIR WELL	☐ RECOMPLETE DIFFERENT FORMATION ☐ TEMPORARY ABANDON	
Jacob Spani	☐ TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL	
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION OTHER	✓ APD EXTENSION	
12. DESCRIBE PROPOSED OR CO	WILDCAT WELL DETERMINATION MPLETED OPERATIONS. Clearly show all pertinents.		OTHER:	
EOG Resources, Inc.	respectfully requests the APD f extended for one year.	or the referenced well be	Approved by the Utah Division of Oil, Gas and Mining	
		D:	ate: November 05, 2009 y: Dollar 1	
NAME (PLEASE PRINT) Mickenzie Gates	PHONE NUMBER 435 781-9145	TITLE Operations Clerk		
SIGNATURE N/A		DATE 11/4/2009		



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43047398570000

API: 43047398570000 **Well Name:** NBU 440-01E

Location: 1882 FSL 1931 FEL QTR NWSE SEC 01 TWNP 100S RNG 200E MER S

Company Permit Issued to: EOG RESOURCES, INC.

Date Original Permit Issued: 12/6/2007

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

require revi	sion. Following is a che	ecklist of some	e items related to t	ne applicati	on, whic	n should be verified	J.
	ated on private land, had a land a la	as the owners	hip changed, if so,	has the sur	face agre	eement been	
	any wells been drilled requirements for this			ell which wo	ould affe	ct the spacing or	
	nere been any unit or o s proposed well?		nts put in place tha	at could affe	ect the po	ermitting or operati	OI
	there been any change the proposed location			wnership, o	or rightof	- way, which could	
• Has tl	ne approved source of	water for drill	ing changed? 📵	Yes 📵 No	0		
	there been any physica je in plans from what v				route wh Yes 🌘	-	
• Is boı	nding still in place, whi	ch covers this	proposed well? 🌘	Yes 🗍	No Uta	roved by the h Division of ias and Mining	
Signature:	Mickenzie Gates	Date: 11/4	/2009				
_	Operations Clerk Repre			Da		November 05, 2009	
					1 01	0.03	

By: Dally

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES			FORM 9	
	5.LEASE DESIGNATION AND SERIAL NUMBER: UTU02270A			
SUNDF	N WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:		
	sals to drill new wells, significantly deepen ex ugged wells, or to drill horizontal laterals. Use		7.UNIT or CA AGREEMENT NAME: NATURAL BUTTES	
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: NBU 440-01E	
2. NAME OF OPERATOR: KERR-MCGEE OIL & GAS ONS	HORE, L.P.		9. API NUMBER: 43047398570000	
3. ADDRESS OF OPERATOR: P.O. Box 173779 1099 18th S	PHONE treet, Suite 600, Denver, CO, 80217 3779	NUMBER: 720 929-6007 Ext	9. FIELD and POOL or WILDCAT: NATURAL BUTTES	
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1882 FSL 1931 FEL			COUNTY: UINTAH	
QTR/QTR, SECTION, TOWNSHI	IP, RANGE, MERIDIAN: Township: 10.0S Range: 20.0E Meridian: S		STATE: UTAH	
11. CHE	CK APPROPRIATE BOXES TO INDICATE	NATURE OF NOTICE, REPORT,	OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION		
✓ NOTICE OF INTENT	☐ ACIDIZE ☐ ☐ CHANGE TO PREVIOUS PLANS ☐	ALTER CASING	☐ CASING REPAIR ☐ CHANGE WELL NAME	
Approximate date work will start: 12/7/2010	CHANGE WELL STATUS	commingle producing formations	CONVERT WELL TYPE	
SUBSEQUENT REPORT Date of Work Completion:	D DEEPEN -	FRACTURE TREAT	NEW CONSTRUCTION	
·	☐ PRODUCTION START OR RESUME	PLUG AND ABANDON RECLAMATION OF WELL SITE	☐ PLUG BACK☐ RECOMPLETE DIFFERENT FORMATION	
SPUD REPORT Date of Spud:	☐ REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	☐ TEMPORARY ABANDON	
	☐ TUBING REPAIR	VENT OR FLARE	WATER DISPOSAL	
DRILLING REPORT Report Date:	WATER SHUTOFF	SI TA STATUS EXTENSION	✓ APD EXTENSION	
	WILDCAT WELL DETERMINATION	OTHER	OTHER:	
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. Kerr-McGee Oil & Gas Onshore, L.P. (Kerr-McGee) respectfully requests an extension to this APD for the maximum time allowed. Please contact the undersigned with any questions and/or comments. Thank you. Utah Division of Oil, Gas and Mining Date: 12/13/2010				
		В	A: Trea Africa	
NAME (PLEASE PRINT) Danielle Piernot	PHONE NUMBER 720 929-6156	TITLE Regulatory Analyst		
SIGNATURE N/A		DATE 12/7/2010		



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43047398570000

API: 43047398570000 **Well Name:** NBU 440-01E

Location: 1882 FSL 1931 FEL QTR NWSE SEC 01 TWNP 100S RNG 200E MER S

Company Permit Issued to: KERR-MCGEE OIL & GAS ONSHORE, L.P.

Date Original Permit Issued: 12/6/2007

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

require revi	sion. Following is a check	list of so	me items related	to the applicat	tion, which should be verified.
	ated on private land, has t ed?	he owne	ership changed, if	so, has the su	rface agreement been
	any wells been drilled in t requirements for this loc			d well which w	rould affect the spacing or
	nere been any unit or othe s proposed well? Yes		= =	e that could aff	ect the permitting or operation
	there been any changes to the proposed location?(ng ownership,	or rightof- way, which could
• Has tl	ne approved source of wa	ter for d	rilling changed?(🧻 Yes 📵 N	lo
	there been any physical c le in plans from what was				route which will require a Yes <a> No
• Is bo	nding still in place, which	covers t	his proposed well	? 📵 Yes 🥘	Approved by the No Utah Division of Oil, Gas and Mining
Signature:	Danielle Piernot		12/7/2010	_	12/13/2010
Title:	Regulatory Analyst Repres	enting:	KERR-MCGEE OIL 8	GAS ONSHOR	PCP: 12/13/2010

RECEIVED December 07, 2010

Sundry Number: 20692 API Well Number: 43047398570000

	STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES		FORM 9	
	5.LEASE DESIGNATION AND SERIAL NUMBER: UTU02270A			
SUND	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:			
	sals to drill new wells, significantly deepen ex agged wells, or to drill horizontal laterals. Use		7.UNIT or CA AGREEMENT NAME: NATURAL BUTTES	
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: NBU 440-01E	
2. NAME OF OPERATOR: KERR-MCGEE OIL & GAS ONS	HORE, L.P.		9. API NUMBER: 43047398570000	
3. ADDRESS OF OPERATOR: P.O. Box 173779 1099 18th S	PHONE treet, Suite 600, Denver, CO, 80217 3779	NUMBER: 720 929-6515 Ext	9. FIELD and POOL or WILDCAT: NATURAL BUTTES	
4. LOCATION OF WELL FOOTAGES AT SURFACE: 1882 FSL 1931 FEL			COUNTY: UINTAH	
QTR/QTR, SECTION, TOWNSHI Qtr/Qtr: NWSE Section: 01	IP, RANGE, MERIDIAN: Township: 10.0S Range: 20.0E Meridian: S		STATE: UTAH	
11. CHE	CK APPROPRIATE BOXES TO INDICATE	NATURE OF NOTICE, REPORT	, OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION		
,	☐ ACIDIZE ☐	ALTER CASING	CASING REPAIR	
Approximate date work will start:	☐ CHANGE TO PREVIOUS PLANS	CHANGE TUBING	☐ CHANGE WELL NAME	
12/6/2011	☐ CHANGE WELL STATUS	COMMINGLE PRODUCING FORMATIONS	☐ CONVERT WELL TYPE	
SUBSEQUENT REPORT	☐ DEEPEN ☐	FRACTURE TREAT	☐ NEW CONSTRUCTION	
Date of Work Completion:	OPERATOR CHANGE	PLUG AND ABANDON	☐ PLUG BACK	
	☐ PRODUCTION START OR RESUME	RECLAMATION OF WELL SITE	☐ RECOMPLETE DIFFERENT FORMATION	
SPUD REPORT Date of Spud:	☐ REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	☐ TEMPORARY ABANDON	
	☐ TUBING REPAIR	VENT OR FLARE	☐ WATER DISPOSAL	
DRILLING REPORT Report Date:	☐ WATER SHUTOFF	SI TA STATUS EXTENSION	✓ APD EXTENSION	
Report Date:	☐ WILDCAT WELL DETERMINATION ☐	OTHER	OTHER:	
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. Kerr-McGee Oil & Gas Onshore, L.P. (Kerr-McGee) respectfully requests an extension to this APD for the maximum time allowed. Please contact the undersigned with any questions and/or comments. Thank you. Approved by the Utah Division of Oil, Gas and Mining Date: 11/30/2011 By:				
NAME (PLEASE PRINT) Danielle Piernot	PHONE NUMBER 720 929-6156	TITLE Regulatory Analyst		
SIGNATURE N/A		DATE 11/29/2011		
137.63		* 11/27/2U11		

Sundry Number: 20692 API Well Number: 43047398570000



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43047398570000

API: 43047398570000 **Well Name:** NBU 440-01E

Location: 1882 FSL 1931 FEL QTR NWSE SEC 01 TWNP 100S RNG 200E MER S

Company Permit Issued to: KERR-MCGEE OIL & GAS ONSHORE, L.P.

Date Original Permit Issued: 12/6/2007

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

• If located on private land, has the ownership changed, if so, has the surface agreement been updated? Yes No
 Have any wells been drilled in the vicinity of the proposed well which would affect the spacing or siting requirements for this location? Yes No
 Has there been any unit or other agreements put in place that could affect the permitting or operation of this proposed well? Yes No
 Have there been any changes to the access route including ownership, or rightof- way, which could affect the proposed location? Yes No
• Has the approved source of water for drilling changed? Yes No
 Have there been any physical changes to the surface location or access route which will require a change in plans from what was discussed at the onsite evaluation? Yes No
• Is bonding still in place, which covers this proposed well? Yes No

Signature: Danielle Piernot **Date:** 11/29/2011

Title: Regulatory Analyst Representing: KERR-MCGEE OIL & GAS ONSHORE, L.P.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT Green River District Vernal Field Office 170 South 500 East Vernal, UT 84078



43 047 39857

JUN 1 3 2012

http://www.blm.gov/ut/st/en/fo/vernal.html

IN REPLY REFER TO: 3160 (UTG011)

Julie Jacobson Anadarko Petroleum Corporation Kerr McGee Oil & Gas Onshore LP 1099 18th Street, Suite 600 Denver, CO 80202

Re:

Notice of Expiration Well No. NBU 440-1E NWSE, Sec. 1, T10S, R20E Uintah County, Utah Lease No. UTU-02270A Natural Buttes Unit

Dear Ms. Jacobson:

The Application for Permit to Drill (APD) for the above-referenced well was approved on October 2, 2008. No extension request of the original APD was received. According to our records, no known activity has transpired at the approved location. In view of the foregoing, this office is notifying you that the approval of the referenced application has expired. If you intend to drill at this location in the future, a new Application for Permit to Drill must be submitted.

This office requires a letter confirming that no surface disturbance has been made for this drill site. Any surface disturbance associated with the approved location of this well is to be rehabilitated. A schedule for this rehabilitation must be submitted to this office. Your cooperation in this matter is appreciated.

If you have any questions regarding this matter, please contact Cindy Severson at (435) 781-4455.

Sincerely,

RECEIVED

JUN 2 1 2012

DIV. OF OIL, GAS & MINING

Assistant Field Manager
Lands & Mineral Resources

cc: UDOGM



State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER

Executive Director

.L

Division of Oil, Gas and Mining JOHN R. BAZA Division Director

June 14, 2012

GREG BELL Lieutenant Governor

> Jenn Hawkins Anadarko Petroleum Corporation 1099 18th Street, Ste. 1800 Denver, CO 80202

43 047 3985 NBU 440-01E 10S 20E 1

Re:

APDs Rescinded for Anadarko Petroleum Corporation

Uintah County

Dear Ms. Hawkins:

Enclosed find the list of APDs that you requested to be rescinded. No drilling activity at these locations has been reported to the division. Therefore, approval to drill these wells is hereby rescinded, effective June 5, 2012.

A new APD must be filed with this office for approval <u>prior</u> to the commencement of any future work on the subject location.

If any previously unreported operations have been performed on this well location, it is imperative that you notify the Division immediately.

Sincerely,

Diana Mason

Environmental Scientist

Can Hlyson

cc:

Well File

Bureau of Land Management, Vernal



43-047-39314	NBU 612-23E
43-047-39317	NBU 610-23E
43-047-39318	NBU 609-23E
43-047-38173	FEDERAL 1021-24O
43-047-40121	HATCH 923-14K
43-047-40122	HATCH 923-24C
43-047-40123	HATCH 923-24E
43-047-38315	BONANZA 1023-15G
43-047-39418	NBU 441-12E
43-047-50519	HATCH 923-14M
43-047-37031	BONANZA 1023-14E
43-047-38746	LOVE 1121-8B
43-047-39797	NBU 606-35E
43-047-39855	NBU 659-01E
<u>→43-047-39857</u>	NBU 440-01E
43-047-39859	NBU 652-06E
43-047-38925	NBU 1022-15N
43-047-39868	NBU 656-01E